



Forever Medical

-40Degree Deep Freezer

The -40 °C deep freezer can control the temperature inside from -15 degree to -40 degree, and set two silicone rubber seals for the out door to keep the better thermal effect and energy saving. Italy computer control system, Germany or Italy compressor used, EMB fan, etc to make sure the better freezing quality for the freezer.



Chest Style

Prices Temperature controlling :

Using Italy micro computer control system, high accuracy sensor to control, display, and warning;

Inner temperature range in -15 to -40°C, digital display.

Microprocessor-based temperature control system.

Safety Functions :

Warning system for high and low temperature, sensor failure, etc;

Warning mode with buzzer, light flashing;

Time-delay prevention when starting up in case of overload current rushing.

Tel: +86-0371-61315851

Web: www.yongjiumed.com

Add: Room 806, Floor 8, Wanda Center, Jinshui District, Zhengzhou, Henan, China

Fax: 0371-61315851

Email: forermed@yjcompany.com

Postcode: 450000



Cooling system :

Full sealed Germany or Italy branded compressor,CFC free high efficiency refrigerant;
Using EMB fan and high efficient evaporator and condensation,quickly freezing and low energy consume;

Excellent cooling system design,freezing quickly,saving energy style;

Thickness foaming WAyer,CFC free thermal material used to keep better thermal effect than reguWARly;

New and environment friendly raw material used.

Humanized design :

Solid door designing,with safety lock and key,better thermal effect ;

Automatic rebound iron hinges designing;

Whole stainless steel inner wall and shelves;

LED digital dispWAY,convenient to watch;

Frost free design,easy to defrost and clean;

Inner LED lighting design;

Wide range of voltage design,range from 187~242 volts,50HZ/60HZ(Optional).

Optional:Temperature recorder,professional WArge door handle for outer door opening easily.

Main Technical Parameters:

Model	Capacity	Temp	External Size W*D*H/mm	Voltage (V/HZ)	Power	Climate	N.W.
YJ-40-60-WA	60	-15 ~ -40 °C	670*755*995	220/50	300	N	70kgs
YJ-40-108-WA	108	-15 ~ -40 °C	900*675*795	220/50	300	N	90kgs
YJ-40-118-WA	118	-15 ~ -40 °C	900*750*920	220/50	300	N	95kgs
YJ-40-208-WA	208	-15 ~ -40 °C	1050*675*795	220/50	350	N	120kgs
YJ-40-218-WA	218	-15 ~ -40 °C	1160*750*860	220/50	350	N	120kgs
YJ-40-308-WA	308	-15 ~ -40 °C	1400*675*795	220/50	400	N	140kgs
YJ-40-318-WA	318	-15 ~ -40 °C	1530*750*860	220/50	400	N	140kgs
YJ-40-460-WA	460	-15 ~ -40 °C	2110*885*1095	220/50	780	N	240kgs
YJ-40-468-WA	468	-15 ~ -40 °C	1400*800*850		550	W	240kgs
YJ-40-568-WA	568	-15 ~ -40 °C	1880*670*795	220/50	600	N	
YJ-40-1000-WA	1000	-15 ~ -40 °C	2265*898*850	220/50	800	N	